



# McDermott Light & Signal

## Navigation Lights for Vessels less than 50 meters

Certified to meet applicable sections of UL 1104


Two miles for vessels less than 50 meters in length.

Years of service without the need for bulb replacement and maintenance

225°  
Screen



**TB5-820-MAST**



**TB5-LED-MAST**  
*older style*

### TB5-820 MAST SPECIFICATIONS:

<b>Range:</b>	5 nautical miles
<b>Mount:</b>	5 1/4" x 5 1/4" Base; 4" x 4" holes on center
<b>Light Source:</b>	High-power LEDs
<b>Material:</b>	High-impact polycarbonate
<b>Visibility Arc:</b>	225 degrees
<b>Power Sources:</b>	12, 24, 32 VDC 120, 220 VAC
<b>Weight:</b>	4 lbs.
<b>Dimensions:</b>	7" h x 5 1/4" l x 5 1/4" w

135°  
Screen



**TB2D-TOW**

112.5°  
Screen



**TB2D-PORT**

### TB2 SPECIFICATIONS:


<b>Range:</b>	2 nautical miles
<b>Mount:</b>	5 1/4" x 5 1/4" Base; 4" x 4" holes on center
<b>Light Source:</b>	High-power LEDs
<b>Material:</b>	High-impact polycarbonate
<b>Visibility Arc:</b>	112.5, 135, 360 degrees
<b>Power Sources:</b>	12, 24, 32 VDC 120, 220 VAC
<b>Weight:</b>	4 lbs.
<b>Dimensions:</b>	6" h x 5 1/4" l x 5 1/4" w

360°



**TB2-78-WHITE**

TOWARDS BOW  
BASE MOUNTING PLATE



FOUR 5/16"  
DIAMETER  
HOLES

4"  
5 1/4"

