



## SUN4 SERIES

High Intensity Solar Light for  
Bridges, Channel Markers, Buoys, etc.



**SUN4-PL**



**SUN4-CASE-FM**

### SPECIFICATIONS:

**Range:** 2 - 6 miles available (See Chart Below)

**Light Source:** High-power LED available in white, red, green, and amber with a rated life of 50,000 hours

**Material:** High-impact UV stabilized polycarbonate

**Voltages:** 12, 24VDC, 120VAC

**Battery:** Rechargeable battery pack with average life of 4-5 years

**Mount:** Raised platform mount

**Flash Rates:** 10, 15, 24, 30, 60 FPM or steady and any IALA flash pattern

**\*Warranty:** One year parts and labor at no charge, except for physical damage or abuse

**SUN4**

| ENCLOSURE | CONFIG   | MODE     | RANGE | FLUX | CANDELA POWER | COLOR | FLASH RATES              |
|-----------|----------|----------|-------|------|---------------|-------|--------------------------|
| PL / CASE | 18L11V6C | STEADY   | 3     | 0.05 | 31.20         | WHITE | 10, 15, 24, 30, & 60 FPM |
|           |          | FLASHING | 4     | 0.10 | 72.50         |       |                          |
|           |          | FLASHING | 5     | 0.18 | 103.60        |       |                          |

|           |          |          |   |      |       |       |                          |
|-----------|----------|----------|---|------|-------|-------|--------------------------|
| PL / CASE | 18L11V6C | STEADY   | 3 | 0.07 | 28.00 | GREEN | 10, 15, 24, 30, & 60 FPM |
|           |          | FLASHING | 4 | 0.17 | 60.10 |       |                          |
|           |          | FLASHING | 5 | 0.45 | 98.70 |       |                          |

|           |          |          |   |      |        |     |                          |
|-----------|----------|----------|---|------|--------|-----|--------------------------|
| PL / CASE | 18L11V6C | STEADY   | 3 | 0.12 | 35.50  | RED | 10, 15, 24, 30, & 60 FPM |
|           |          | FLASHING | 4 | 0.25 | 71.90  |     |                          |
|           |          | FLASHING | 5 | 0.56 | 117.70 |     |                          |

|           |          |          |   |      |       |       |                          |
|-----------|----------|----------|---|------|-------|-------|--------------------------|
| PL / CASE | 18L11V6C | STEADY   | 3 | 0.11 | 29.90 | AMBER | 10, 15, 24, 30, & 60 FPM |
|           |          | FLASHING | 4 | 0.23 | 53.30 |       |                          |
|           |          | FLASHING | 5 | 0.75 | 83.60 |       |                          |

\*PL = PLATFORM MOUNT

\*NM = NAUTICAL MILES

\*SPK = 2 BIRD SPIKES

\*PM = PIPE MOUNT

\*FM = FLAT MOUNT

\*MAG = MAGNETIC MOUNT

\*CASE = BLACK BOX

