

# WARNING LIGHTS: SIGNAL

A complete line of warning lights for signaling trouble or notification. Made in voltage ranges from 6 volts to 240 volts AC or DC. All lenses constructed of Lexan.

**(A) MODEL: SERIES-9**

**UNIVERSAL MODEL** - High optic lens as shown. Available in flat mount (3 screws) or pipe mount (3/4" npt).

*Size: 5" High - 4" Diameter*

**(B) MODEL: SERIES DCL**

This unit has a larger base which allows for using standard screw-in lamps. Available as shown with 3/4" nipple. Also available with longer pipe nipple mounting flange.

*Size: 8 1/4" High - 5" Diameter*

**(C) MODEL: SERIES 266**

This unit was designed to give maximum output in the smallest size fixture. Has high optic unbreakable lens.

*Size: 4" High - 2.650" Diameter*

**(D) MODEL: SERIES WB**

This unit is similar to models 9 and DCL types but this is mounted on a waterproof square box. This allows connecting in a straight line through the conduit.

*Size: 7 3/4" High - 4 3/4" Square*

**SUFFIXES:**

- \*C - Chrome Bezel
- \*BLK - Black Bezel
- \*SSF - Solid State Flasher
- \*PM - Pipe Mount
- \*FM - Flat Mount
- \*BH - Beehive Lens as shown in Figure D

A)



**SERIES 9**

B)



**SERIES DCL**

C)



**SERIES 266**

D)



**SERIES WB**